

Exam : Juniper Networks JN0-304

Title : M-series,Specialist(JNCIS-M)

Version : Demo

1. Routers A and B have an OC12c and a GE link between them and are running OSPF over both of these links. Which statement is correct, assuming the default JUNOS software OSPF metric calculation?

- A. There are two equal cost paths between A and B.
- B. The GE link is the preferred path between A and B.
- C. The OC12c link is the preferred path between A and B.
- D. Manual metric assignment must be configured to determine the outcome.

Answers: A

2. What is the default function of a secondary path in MPLS?

- A. to act as an equal-cost path to the primary path
- B. to enable another LSP for load balancing
- C. to act as a diverse backup path to the primary path
- D. to allow the use of explicit path selection via EROs

Answers: C

3. How long is an IPv6 address?

- A. 32 bits
- B. 64 bits
- C. 128 bits
- D. 256 bits

Answers: C

4. Which three are well-known mandatory BGP attributes? (Choose three.)

- A. Origin
- B. AS path
- C. Next hop
- D. Community
- E. Multiple exit discriminator

Answers: ABC

5. In which two ways can you influence how downstream LSRs treat MPLS traffic? (Choose two.)

- A. Use an EXP rewrite table.
- B. Use a DSCP rewrite table.
- C. Statically assign a CoS value to an LDP-signaled LSP.
- D. Statically assign a CoS value to an RSVP-signaled LSP.

Answers: AD

6. Which three authentication options does IS-IS support? (Choose three.)

- A. MD5
- B. DES
- C. Kerberos
- D. unauthenticated
- E. simple password

Answers: ADE

7. Two Label-Switched Paths called LSP A and LSP B have been configured on a router. LSP A has been configured with a hold-priority of 3. There is insufficient reservable bandwidth along the path to accommodate both LSPs reservation requirements. Which setup priority must LSP B have to pre-empt LSP A and use its bandwidth?

- A. 2
- B. 3
- C. 4
- D. 7

Answers: A

8. OSPFv3 is used to route which type of packets?

- A. IPv4
- B. IPv6
- C. MPLS
- D. IS-IS

Answers: B

9. Which three are used to create a separate multicast and unicast forwarding topology on a Juniper Networks router? (Choose three.)

- A. MBGP
- B. RIB groups
- C. firewall filters
- D. routing policy
- E. filter based forwarding (FBF)

Answers: ABD

10. Which two statements about IS reachability TLV (TLV 2) and the extended IS reachability (TLV 22) are true? (Choose two.)

- A. TLV 22 supports wide metrics.
- B. TLV 2 is only used in Level 1 routers.
- C. TLV 22 displays the neighbor's extended areas.
- D. Only TLV 22 can support the inclusion of sub-TLVs.

Answers: AD